



PC board isolation column

PC board isolation column

Material: UL qualified NYLON66 (character), fire rating 94V-2, good insulation, not easy to aging.

Usage: The first substrate drilling, and then the isolation column from the bottom up push into the fixed, then the PC board can be fixed.

Features: PC board can be fixed without tools; it is easy to disassemble when replacing or repairing PC board.

Special offer a limited number of while stocks last, the large price is better.

Isolation column PC board isolation column

Specification

Item no	pcs	price
CS-1625	2900	0.6084
MMR-10	6000	0.556
SP-3	700	0.12
PS-6	400	0.289
MSPDLN-15.9	719	0.319
PS-5	6100	0.15
PS-28	1000	0.26
PS-19	600	0.21
PS-13	800	0.2
PS-16	900	0.27
PS-22	1000	0.23
PS-25	900	0.24
PS-36	1000	0.25
DLCBS3-6.4	1560	0.395
SP-MDL-1-14.0	1000	0.456
MSPDLN-3.2	4800	0.259
MCBP-19.1	1099	0.395
LED3.2/7-2.5	4840	0.064
LED4.2/7-8.0	900	0.057
B-LED2.8/4.0-3.5	2000	0.52
MSPDLN-12.7	8000	0.319

Product Show



