



PL male right angle pipe joint

PL male right angle pipe joint

Material: plastic socket: POM, body: PBT, adapter: brass

Operating pressure range: 0-10kgf/cm²

Operating temperature range: -20~70°C


General hose: PU tube or nylon hose

Color: plastic socket: blue, body: black, adapter: brass (not electroplated)

1. It has a variety of models and specifications and is used in various pneumatic systems.
2. Excellent flow performance, can pass the flow of the same volume as the inner diameter of the trachea.
3. The threaded part is coated with sealant to ensure that there is no leakage in the threaded connection part.

PL male right angle pipe joint

Specification



Item No.	OD	Connection thread/R	Package /PCS
PL4-M5	4	M5×0.8	100
PL4-01	4	PT1/8	100
PL4-02	4	PT1/4	100
PL4-03	4	PT3/8	100
PL4-04	4	PT1/2	100
PL6-M5	6	M5×0.8	100
PL6-01	6	PT1/8	100
PL6-02	6	PT1/4	100
PL6-03	6	PT3/8	100
PL6-04	6	PT1/2	100
PL8-01	8	PT1/8	100
PL8-02	8	PT1/4	100
PL8-03	8	PT3/8	100
PL8-04	8	PT1/2	100
PL10-01	10	PT1/8	50
PL10-02	10	PT1/4	50
PL10-03	10	PT3/8	50
PL10-04	10	PT1/2	50
PL12-01	12	PT1/8	50
PL12-02	12	PT1/4	50
PL12-03	12	PT3/8	50
PL12-04	12	PT1/2	25

Product Show



耐高压 & 不脱扣

能够承受更大更强而不脱扣，安装方便，使用寿命长

精工压铸

坚固耐用

杜绝漏气



360°转动



满足布管需求

简单灵巧，型号多样，可以满足任何布管需求。即使安装后，管体也可以360°转动



EXQUISITE QUALITY

严格工艺精湛品质

更精密的工艺更高品质的产品

3-800 COMMITMENT TO LET YOU IN SOONER FURTHER STRICT WORKMANSHIP

EXQUISITE QUALITY SHIPPING WORLD FREE



抗腐蚀强



经久耐用



抗温性强



品质保障



不生锈







