



Round bare terminal R

Series: R

Product Material: Terminal made of high quality copper, good conductivity.

Features: The use of high-quality matte plating, greatly extended anti-rust time, no sharp parts; supporting the daily terminal crimping tools can be pressed wire, beautiful wiring,

International Certification: EU RoHS environmental certification.

Product Features: Good quality, no crack after cracking open, -40 degrees heat to 150 degrees normal use.

How to use: peel the wire skin, into the terminal after the brass

Connecting terminal connecting terminal cold pressing terminal

Specification

Item No.	DIMENSION (mm)				
	USA screw	D2	W	F	L
R1.25-3 connection	#4	3.2	5.7	4.95	12.6
RS1.25-3.5 connection	#6	3.7	5.7	4.95	12.6
RM1.25-3.5 connection	#6	3.7	6.6	6.3	14.4
RL1.25-3.5 connection	#6	3.7	8.0	7	15.8
RS1.25-4 connection	#8	4.3	6.6	6.3	14.4
RL1.25-4 connection	#8	4.3	8.0	7	15.8
RS1.25-5 connection	#10	5.3	8.0	7	15.8
RL1 25-5 connection	#10	5.3	9.8	8.5	18
RS1.25-6 connection	1/4	6.4	9.8	8.5	18
RL1.25-6 connection	1/4	6.4	11.6	11.1	21.8
R1.25-8 connection	5/16	8.4	11.6	11.1	21.8
R1.25-10 connection	3/18	10.5	13.6	13.9	25.5
R2-3 connection	#4	3.2	6.6	4.3	12.3
RS2-3.5 connection	#6	3.7	6.6	4.3	12.3
RM2-3.5 connection	#6	3.7	6.6	7	16
RL2-3.5 connection	#6	3.7	8.5	7.75	16.8
RS2-4 connection	#8	4.3	6.6	7	16
RL2-4 connection	#8	4.3	8.5	7.75	16.8
RS2-5 connection	#10	5.3	8.5	7.75	16.8
RL2-5 connection	#10	5.3	9.5	7.25	16.8
RL2-6 connection	1/4	6.4	12.0	11	21.8
R2-8 connection	5/16	8.4	12.0	11	21.8
R2-10 connection	3.18	10.5	14.6	13.9	26
R3.5-4 connection	#8	4.3	8.0	7.7	18
RS3.5-5 connection	#10	5.3	8.0	7.7	18
RL3.5-5 connection	#10	5.3	12.0	7.7	21.4
R3.5-6 connection	1/4	6.4	12.0	7.7	21.4
R3.5-8 connection	5/16	8.4	15.0	14	27.5
R3.5-10 connection	3/18	10.5	15.0	14	27.5
R5.5-3.5 connection	#6	3.7	7.2	5.9	15.7